

TOSHIBA

e-STUDIO™ 5528A/6528A

- High-Speed – Up to 55 & 65 PPM
- High-Volume
- Advanced Security Features
- Solutions Ready
- Environmentally Friendly



MAIN SPECIFICATIONS

Copy Process	Indirect Electrostatic Photographic (OPC)/Laser Printing/Heat Roller Fusing
Display	10.1" Color WSVGA Touch Screen Tilting Display
Copy Speed	55/65 PPM (LT)
Warm-Up Time	Monochrome: Less Than 4.3/4.3 Seconds From Powering on: Approx. 26 Seconds From Sleep & Low Power: Less Than 20 Seconds
Copy Resolution	600 x 600 dpi
Stack Feed Bypass	3.9" x 5.8" to 12.5" x 18", 12" x 47" Banner, Envelope
Multiple Copying	Up to 999 Copies
Paper Capacity	Standard 1,200 Sheets/Max. 5,200 Sheets
Original Feed	300-Sheet DSDF or DSDF with Double Feed Detection or 100-Sheet RADF
Scan Speed & Weights	DSDF Scan: 70IPM, (Monochrome or Color), Simplex or Duplex: 9.3-110lb Bond RADF Scan: 50IPM, (Monochrome or Color), Simplex: 9.3-41.8lb Bond Duplex: 13.3-41.8lb Bond LD/A3 Drawer 1: 550 Sheets-ST-R to LD Drawer 2: 550 Sheets-ST-R to 12.5" x 18" Stack Feed Bypass: 100 Sheets-3.9" x 5.8" to 12.5" x 18", 12" x 47" Banner Opt. 550-Sheet Paper Feed Pedestal-ST-R to 12.5" x 18" Opt. 550-Sheet Drawer for PFP-ST-R to 12.5" x 18" Opt. Envelope Cassette for PFP-Approx. 60 Envelopes/550 Sheets-ST-R to LG Opt. 2,000-Sheet Tandem LCF (Pedestal Type)-LT Only Opt. 2,000-Sheet External LCF-LT Only Standard: 550 Sheets x 2-16lb Bond-110lb Cover Stack Feed Bypass: 100 Sheets-14lb Bond-110lb Cover Banner up to 90lb Index Opt. 550-Sheet Paper Feed Pedestal-16lb Bond-140lb Index Opt. 550 Sheets Drawer for PFP-16lb Bond-110lb Cover Opt. Envelope Cassette for PFP-16lb Bond-110lb Cover Opt. 2,000-Sheet Tandem LCF (Pedestal Type)-16lb Bond-110lb Cover Opt. 2,000-Sheet External LCF-LT-16lb Bond-110lb Cover Standard Automatic Duplex Unit (16lb Bond-140lb Index)
Max. Original Size	25% to 400%
Paper Feed Sizes	Max. 223K/243K Month Approx.159lb 26" (W) x 25.2" (D) x 41.2" (H) 39.8K @ 5%
Paper Weights	120 Volts, 50/60 Hz, 12 Amps Maximum 1.8kW (120V) NEMA 5-15 6GB 128GB Solid State Drive (SSD)
Duplex	
Reproduction Ratio	
Max Duty Cycle	
Weight	
Approx. Dimensions	
Toner Yield	
Power Source	
Power Consumption	
Plug Type	
Memory	
Hard Disk Drive	

e-BRIDGE NEXT PRINT SPECIFICATIONS

PDL	PCL5e, PCL5c, PCL6 (PCL XL), PS3, PDF, XPS, JPEG
Print Resolution	600 x 600 dpi (5 bit), 1,200 x 1,200 dpi (2 bit) or 3,600 (Equivalence) x 1,200 dpi (BW/with Smoothing) (PS3 Only)
Operating Systems	Windows® 8.1, 10, 11, Windows Server® 2012/R2, Windows Server® 2016/19/22, Macintosh® (macOS X 10.10-15, 12), Unix®, Linux®
Network Protocols	TCP/IP (IPv4, IPv6), NetBIOS over TCP/IP, IPX/SPX® for Novell®
Printing Protocols	Environments, EtherTalk for Macintosh Environments SMB V1-3, LPR/LPD, IPP V1.2 w/Authentication (TLS 1.2/1.3), AppleTalk® PAP or EtherTalk, Port 9100 (Bi-Directional), NetWare P-SERVER LPD w/iPrint, Bluetooth (HCRP/BI/OPP/FTP), WS Print, FTP
Print Drivers	Windows® 8.1 (32-bit, 64-bit), Windows Server® 2012/R2 (64-bit), Windows Server® 2016/19/22, Windows® 10, 11 (64-bit), macOS X 10.12-15, 11, 12
Interface	RJ-45 Ethernet (10/100/1000 Base-T), USB 2.0 (High-Speed) Optional IEEE802.11b/g/n, Wireless LAN, Optional Bluetooth
Wireless Device	AirPrint®, Mopria®, e-BRIDGE Print & Capture Application on iOS and Android (Available via Apple® App Store or Google Play)
Device Management	TopAccess
Account Control	Up to 10,000 Users or 1,000 Departments Supports User Authentication (on Device), Login Name/Password (via Windows® Domain) or Login Name/Password (via LDAP Server) for Copy, Print, Scan, Fax, List, and User Function
Accessibility Features	Tilt Front Panel, Job Programs, Universal Grip for Paper Trays, Disable Screen Timeout, Audible Beeps, Optional Voice Assist



Security Features

User Authentication, Trusted Platform Module, On-Board Data Scramble Function, SCEP, Disable, e-Filing, Disable Copy, Disk Overwrite, IP Address Filtering (10 Sets), MAC Address Filtering (10 Sets), Network Service Control, Network Port Control, SMB Packet Signing, SSL/TLS (HTTP, IPP, LDAP, SMTP, POP, FTP, DPWS, SYSLOG), IPsec (IKEv1, IKEv2), Security Mode Change, CC Certified (ISO/IEC15408)* with HCD-PP v1.0, IEEE802.1X (Wired/Wireless), Digital Signature for Client Utilities, Password Policy, Password Lock, Password Expiration, Self Testing, Job Access Control, Log Access Control for Job Log, Security Stamp, Role Based Access Control, Secure PDF, Digital Signature for Firmware Update, Integrity Check Function, Image Log, Card Authentication, Biometric Authentication
*Conformance with HCD-PPv1.0 in High Security Mode
ENERGY STAR® (V3.1), EPEAT Gold, Californian Proposition 65
WHQL (Windows® 8, 8.1, 10, 11, 2012, 2012 R2, 2016/19/22), Novell®, Citrix®, SAP, AirPrint® and Mopria®

Environmental Standards Certifications

SCAN SPECIFICATIONS

Scan Speed	DSDF Scan: Up to 240 IPM Duplex, 120 IPM Simplex (Monochrome or Color) RADF Scan: Up to 73 IPM (Monochrome or Color)
Scan Modes	Standard: Full Color, Auto Color, Monochrome, Grayscale
OCR	DOC/XLS/PPT/PDF
Scan Resolution	600 dpi, 400 dpi, 300 dpi, 200 dpi, 150 dpi, 100 dpi
File Formats	Monochrome: TIFF-Multi/Single Page, PDF-Multi/Single Page, PDF/A, Searchable PDF, XPS-Multi/Single Page, DOCX, XLSX, PPTX Color/Grayscale: JPEG, TIFF-Multi/Single Page, PDF-Multi/Single Page, PDF/A, Slim PDF, Searchable PDF, XPS-Multi/Single Page, DOCX, XLSX, PPTX
Image Compression	Color/Grayscale: JPEG (High, Middle, Low)

FACSIMILE SPECIFICATIONS

Compatibility	Super G3
Data Compression	MH/MR/MMR/JBIG
Transmission Speed	Approx. 3 Seconds Per Page
Fax Modem Speed	Up to 33.6 Kbps
Memory Transmission	100 Jobs (with HDD), 2,000 Destinations Max. 400 Destinations/Job
Scan Speed	0.7 Seconds Per Page, Maximum 73 IPM

e-FILING SPECIFICATIONS

Operation Method	Color Touch Screen Control Panel or Client PC
Number of Boxes	1 Public Box, 200 Private User Boxes
Capacity of Boxes	100 Folders Per Box, 400 Documents Per Folder/Box, 200 Pages Per Document

ACCESSORIES (OPTIONS)

Platen & Document Feeder Options		Unicode Font Enabler	GS1007NODE
DSDF	MR4010	Multi-Station Print Enabler	
DSDF with Double Feed Detection	MR4020	Per Seat License	GS1090NODE
RADF	MR3033	e-BRIDGE Plus for OneDrive	
Platen Cover	KA5005PC	for Business V3.0	GB2300NODE
Additional Paper Options		e-BRIDGE Plus for SharePoint	
Paper Feed Pedestal	KD1072	Online V3.0	GB2310NODE
Drawer Module	MY1052	e-BRIDGE Plus for Exchange	
Envelope Cassette Option	MY1053	Online V3.0	GB2320NODE
Large Capacity Feeder	KD1073LT	e-BRIDGE Plus for Gmail	GB2380NODE
External Large Capacity Feeder	MP2002L	e-BRIDGE Plus for Google Workspace	GB2390NODE
Finishing Options		Security SSD (512GB)	GE1280
65-Sheet Staple Finisher	MJ1113	FIPS HDD (320GB)	GE1260
65-Sheet Saddle-Stitch Finisher	MJ1114	e-BRIDGE Plus Voice Guidance	GB2540NODE
Hole Punch for MJ1113/MJ1114	MJ6107N	e-BRIDGE Global Print	GB2550NODE
Bridge Kit	KN5005	Miscellaneous Options	
Job Separator	MJ5015	Card Reader Holder	GR1320
Connectivity/Security Options		Accessory Tray	GR1330
FAX Unit/2 nd Line for FAX Unit	GD1370N	Panel 10-Key Option	GR1340
Wireless LAN/Bluetooth	GN4030A3	Stand	STAND5015
Fax Over IP License Key	GS1100NODE	Work Tray	KK5005
Bluetooth Keyboard	GR9001	Manual Pocket	KK5008
2 nd NIC Holder	GR1430	Harness for Coin Controller	GQ1280
USB Hub	GR1420	Accessible Arm	KK2560
Meta Scan Enabler	GS1010NODE		
IPSec Enabler	GP1080NODE		

Designs and specifications subject to change without notice. Specifications may vary by conditions of use and/or environmental usage. For best results and reliable performance, always use supplies manufactured or designated by Toshiba. Not all options and accessories may be available at the time of product launch. Please contact a local Authorized Toshiba Dealership for availability. Toner yields are estimates based on 5% coverage, letter-size page. Driver and connectivity feature support varies by client/network operating system. Product names may be trademarks of their respective companies. AirPrint® and the AirPrint® logo are trademarks of Apple Inc. This is a Class 1 laser product complying with IEC60825-1. All company and/or product names are trademarks and/or registered trademarks of their respective manufacturers in their markets and/or countries.

Corporate Office

25530 Commercentre Drive, Lake Forest, CA 92630
Tel: 949-462-6000

East Coast

959 Route 46 East, 5th Floor, Parsippany, NJ 07054
Tel: 973-316-2700

Midwest

8770 W. Bryn Mawr Ave., Suite 700, Chicago, IL 60631
Tel: 773-380-6000

South

2037 Bakers Mill Rd., Dacula, GA 30019
Tel: 678-546-9385

West Coast

25530 Commercentre Drive, Lake Forest, CA 92630
Tel: 949-462-6000

Website

www.business.toshiba.com